

AMENDMENTS TO THE CLAIMS:

Please amend the claims as follows:

1. (Currently Amended) An arrayed waveguide grating having a slab-waveguide, the slab-waveguide comprising:

a plurality of input ports for inputting signals of different wavelengths in correspondence to these wavelengths;

an output port disposed on ~~the~~ a focus position of the 0-th order diffraction beams inputted from the input ports for outputting a signal obtained as a result of multiplexing of the individual wavelengths; and

a monitor signal port disposed on ~~the~~ a focus position of higher order diffraction beams other than the 0-th order diffraction beams obtained from the signals inputted from the plurality of input ports for monitoring the multiplexed signal.

2. (Original) An arrayed waveguide grating having a slab-waveguide, the slab-waveguide comprising:

a plurality of input ports for inputting signals of different wavelengths in correspondence to these wavelengths;

an output port disposed on the focus position of the 0-th order diffraction beams inputted from the input ports for outputting a signal obtained as a result of multiplexing of the individual wavelengths; and

a higher order diffraction beam reflecting means disposed on the focus position of higher order diffraction beams other than the 0-th order obtained from the signals inputted from the input ports for reflecting the higher order diffraction beams to the side of the plurality of input ports.

3. (Currently Amended) An arrayed waveguide grating having a slab-waveguide, the slab-waveguide comprising:

a plurality of input ports for inputting signals of different wavelengths in

correspondence to these wavelengths;

an output port disposed on the focus position of the 0-th order diffraction beams inputted from the input ports for outputting a signal obtained as a result of multiplexing of the individual wavelengths;

a higher order diffraction beam reflecting means disposed on the focus position of higher order diffraction beams other than the 0-th order obtained from the signals inputted from the input ports for reflecting the higher order diffraction beams to the side of the plurality of input ports; and

~~one or more~~ at least one monitor signal ~~ports~~ port disposed at a position or positions other than the plurality of input ports for taking out a signal or signals reflected from the higher order diffraction beam reflecting means.

4. (Currently Amended) An optical transmission system comprising:

a plurality of signal sources each provided for each ~~peculiar~~ individual wavelength; ;
an input waveguide for inputting signals of different wavelengths from these signal sources in correspondence to these wavelengths; ;

a channel waveguide array ~~having~~ comprising waveguides with lengths progressively increasing by a predetermined waveguide length difference; ;

an input side slab-waveguide inter-connecting the input side of the channel waveguide array and the input waveguide; ; and

an output side slab-waveguide which ~~has~~ comprises:
output ports inter-connecting to the output side of the channel waveguide array and disposed at the focus position of the 0-th order diffraction beams inputted from the input waveguides through the input side slab-waveguide and the channel waveguide array for outputting a wavelength multiplexed signal;

an output waveguide connected to the output port for outputting the multiplexed signal to be transmitted;

a monitor signal separating means for demultiplexing, by using the channel waveguide array, the multiplexed signal obtained in the output side slab-waveguide at the

focus position of higher order diffraction beams other than the ~~0-th~~ 0-th order obtained from the signals from the input waveguide, thereby separating the monitor signals of wavelengths corresponding to those of the signals inputted from the input waveguides;

an output level detecting means for detecting, from the signals of different wavelengths obtained from the monitor signal separating means, the output levels of the individual wavelength signals from the plurality of signal sources; and

a signal source power control means for controlling the power levels of the plurality of signal sources according to the output levels of the individual wavelength signals from the plurality of signal sources as detected by the output level detecting means.

5. (Currently Amended) An optical transmission system comprising:

a plurality of signal sources each provided for each ~~peculiar~~ individual wavelength;

an input waveguide for inputting signals of different wavelengths from these signal sources in correspondence to these wavelengths;

a channel waveguide array having waveguides with lengths progressively increasing by a predetermined waveguide length difference;

an input side slab-waveguide inter-connecting the input side of the channel waveguide array and the input waveguide;

an output side slab-waveguide ~~including~~ comprising:

an output port connected to the output side of the channel waveguide array and disposed at the focus position of the 0-th order diffraction beams inputted from the input waveguides through the input side slab-waveguide and the channel waveguide array for outputting a wavelength multiplexed signal; and

a monitor signal port disposed at the focus position of higher order diffraction beams other than the 0-th order obtained from the signals inputted from the input waveguide;

an output waveguide connected to the output port for outputting the multiplexed signal to be transmitted;

a monitor signal separating means for demultiplexing ~~or separating~~, by using the channel waveguide array, the individual wavelength monitor signals from the wavelength

multiplexed signal obtained from the monitor port;

an output level detecting means for detecting, from the signals of individual wavelengths obtained from the monitor signal separating means, the output levels of the individual wavelength signals from the plurality of signal sources; and

a signal source power control means for controlling the power levels of the plurality of signal sources according to the output levels of the individual wavelength signals from the plurality of signal sources as detected by the output level detecting means.

6. (Currently Amended) An optical transmission system comprising:

an input waveguide for inputting signals of different wavelengths in correspondence to these wavelengths;

a channel waveguide array ~~having~~ comprising waveguides with lengths progressively increasing by a predetermined waveguide length difference;

an input side slab-waveguide inter-connecting the input side of the channel waveguide array and the input waveguide;

an output side slab-waveguide including an output port connected to the output side of the channel waveguide array and disposed at the focus position of the 0-th order diffraction beams inputted from the input waveguides through the input side slab-waveguide and the channel waveguide array for outputting a wavelength multiplexed signal;

an output waveguide connected to the output port for outputting the multiplexed signal to be transmitted;

a monitor signal separating means for demultiplexing or separating, by using the channel waveguide array, the multiplexed signal obtained at the focus position of higher order diffraction beam other than 0-th order of the multiplexed signals inputted from the input waveguide in the output slab-waveguide to obtain the individual wavelength monitor signal signals;

an output level detecting means for detecting, from the signals of individual wavelengths obtained from the monitor signal separating means, the output levels of the individual wavelength; and

a signal incidence level control means for controlling the incidence levels of the individual wavelength signal signals incident on the plurality of input waveguides according to the output levels of the individual wavelength signals as detected by the output level detecting means.

7. (Currently Amended) An optical transmission system comprising:

a plurality of input waveguides for inputting signals of different wavelengths in correspondence to these wavelengths;

a channel waveguide array ~~having~~ comprising waveguides with lengths progressively increasing by a predetermined waveguide length difference;

an input side slab-waveguide inter-connecting the input side of the channel waveguide array and the input waveguide;

an output side slab-waveguide ~~including~~ comprising:

an output port connected to the output side of the channel waveguide array and disposed at the focus position of the 0-th order diffraction beams inputted from the input waveguides through the input side slab-waveguide and the channel waveguide array for outputting a wavelength multiplexed signal and a monitor signal port disposed at the focus position of higher order diffraction beams other than the 0-th order obtained from the signal inputted from the input waveguide;

an output waveguide connected to the output port for outputting the multiplexed signal to be transmitted;

a monitor signal separating means for demultiplexing or separating, by using the channel waveguide array, the wavelength multiplexed signal obtained from the monitor port to obtain the individual wavelength monitor outputs;

an output level detecting means for detecting, from the signals of individual wavelengths obtained from the monitor signal separating means, the output levels of the individual wavelength; and

a signal incidence control means for controlling the incidence levels of the individual wavelength signals incident on the plurality of input waveguides according to the output

levels of the individual wavelength signals as detected by the output level detecting means.

8. (Currently Amended) An optical transmission system comprising:

an input waveguides for inputting signals of different wavelengths in correspondence to these wavelengths;

a channel waveguide array ~~having~~ comprising waveguides with lengths progressively increasing by a predetermined waveguide length difference;

an input side slab-waveguide inter-connecting the input side of the channel waveguide array and the input waveguide;

an output side slab-waveguide, ~~including~~ comprising:

an output port connected to the output side of the channel waveguide array and disposed at the focus position of the 0-th order diffraction beams inputted from the input waveguides through the input side slab-waveguide and the channel waveguide array for outputting a wavelength multiplexed signal;

an output waveguide connected to the output port for outputting the multiplexed signal to be transmitted; and

a monitor signal separating means for demultiplexing or separating, by using the channel waveguide array, the multiplexed signal obtained at the focus position of higher order diffraction beam other than 0-th order of the multiplexed signals inputted from the input waveguide in the output slab-waveguide to obtain the individual wavelength monitor signal outputs.

9. (Currently Amended) An arrayed waveguide grating comprising:

an input waveguides for inputting signals of different wavelengths in correspondence to these wavelengths;

a channel waveguide array ~~having~~ comprising waveguides with lengths progressively increasing by a predetermined waveguide length difference;

an input side slab-waveguide inter-connecting the input side of the channel waveguide array and the input waveguides ~~and having~~ comprising:

monitor signal ports for monitoring signals returning from the channel waveguide array;

an output side slab-waveguide ~~including an output side slab-waveguide including~~ comprising:

an output port connected to the output side of the channel waveguide array and disposed at the focus position of the 0-th order diffraction beams inputted from the input waveguides through the input side slab-waveguide and the channel waveguide array for outputting a wavelength multiplexed signal and a signal returning means for causing a signal converged on the focus position of higher order diffraction beams other than the 0-th order obtained from the signals inputted from the input waveguides to return from the focus position to the input side; and

an output waveguide connected to the output port for obtaining the multiplexed signal.

10. (Currently Amended) The arrayed waveguide grating according to claim 9, wherein the signal returning means is comprises:

a reflecting means disposed at the focus position of higher order diffraction beams other than the 0-th order obtained from the signals inputted from the input waveguides for reflecting the higher order diffraction beams to the side of the plurality of input waveguides.

11. (Currently Amended) An arrayed waveguide grating comprising:

a substrate;

input waveguides disposed on the substrate for inputting signals of individual wavelengths in correspondence thereto;

a channel waveguide grating disposed on the substrate and having waveguides with lengths progressively increasing by a predetermined waveguide length difference;

an input side slab-waveguide disposed on the substrate and inter-connecting the input side of the channel waveguide array and the input waveguides;

an output side slab-waveguide connected to the output side of the channel waveguide array and disposed at the focus position of the 0-th diffraction beams obtained from the

signals inputted from the input waveguides through the input side slab-waveguide and the channel waveguide array for outputting a wavelength multiplexed signal; and

a monitor signal port disposed at the focus position of higher order diffraction beams other than the 0-th order obtained from the signals inputted from the input waveguides;

an output waveguide connected to the output port;

a waveguide disposed on the substrate ~~and having~~ comprising:

~~one~~ a first terminal connected to the monitor signal port of the output side slab-waveguide; and

~~the other~~ a second terminal disposed on the inner side of one end face of the substrate; and

a reflecting means disposed at the ~~other~~ second terminal of the waveguide for reflecting the signal led out from the monitor signal port.

12. (Currently Amended) An arrayed waveguide grating comprising:

a substrate;

input waveguides disposed on the substrate for inputting signals of individual wavelengths in correspondence thereto;

a channel waveguide grating disposed on the substrate and having waveguides with lengths progressively increasing by a predetermined waveguide length difference;

an input side slab-waveguide disposed on the substrate and inter-connecting the input side of the channel waveguide array and the input waveguides;

an output side slab-waveguide connected to the output side of the channel waveguide array ~~and having~~ comprising:

a wavelength multiplexed signal output port disposed at the focus position of the 0-th diffracted signals obtained from the signals inputted from the input waveguides through the input side slab-waveguide and the channel waveguide array; ;

a monitor signal output port disposed at the focus position of the higher order diffraction beams other than the 0-th order diffraction beams obtained from the signals inputted from the input waveguides; and

a monitor signal input port for outputting an output from a predetermined path, through which the signal outputted from the monitor signal output port returns, toward the side of the plurality of input waveguides;

an output waveguide connected to the output port; and

a waveguide disposed on the substrate and optically connecting the monitor signal output port and monitor signal input port.

13. (Currently Amended) An arrayed waveguide grating comprising:

a substrate;

input waveguides disposed on the substrate for inputting signals of individual wavelengths in correspondence thereto;

a channel waveguide grating disposed on the substrate ~~and having~~ comprising waveguides with lengths progressively increasing by a predetermined waveguide length difference;

an input side slab-waveguide disposed on the substrate and inter-connecting the input side of the channel waveguide array and the input waveguides;

an output side slab-waveguide connected to the output side of the channel waveguide array ~~and having~~ comprising:

a wavelength multiplexed signal output port disposed at the focus position of the 0-th diffracted signals obtained from the signals inputted from the input waveguides through the input side slab-waveguide and the channel waveguide array; ; and

a monitor signal port disposed at the focus position of the higher order diffraction beams other than the 0-th order diffraction beams obtained from the signals inputted from the input waveguides;

an output waveguide connected to the output port;

a waveguide disposed on the substrate ~~and having~~ comprising:

~~one~~ a first terminal connected to the monitor signal port of the output side slab-waveguide ; and

~~the other~~ a second terminal disposed on one end face of the substrate; and

a reflecting means disposed on the other terminal of the waveguide for reflecting the signal led out from the monitor signal port.

14. (Currently Amended) An arrayed waveguide grating comprising:

a substrate;

input waveguides disposed on the substrate for inputting signals of individual wavelengths in correspondence thereto;

a channel waveguide grating disposed on the substrate ~~and having~~ comprising waveguides with lengths progressively increasing by a predetermined waveguide length difference;

an input side slab-waveguide disposed on the substrate and inter-connecting the input side of the channel waveguide array and the input waveguides;

an output side slab-waveguide connected to the output side of the channel waveguide array ~~and having~~ comprising:

a wavelength multiplexed signal output port disposed at the focus position of the 0-th diffracted signals obtained from the signals inputted from the input waveguides through the input side slab-waveguide and the channel waveguide array; ;

a monitor signal output port disposed at the focus position of the higher order diffraction beams other than the 0-th order diffraction beams obtained from the signals inputted from the input waveguides; and

a monitor signal input port for outputting an output from a predetermined path, through which the signal outputted from the monitor signal output port returns, toward the side of the plurality of input waveguides;

a monitor signal output waveguide disposed on the substrate ~~and having~~ comprising:

~~one~~ a first terminal connected to the monitor signal port of the output side slab-waveguide; and

~~the other~~ a second terminal disposed on one end face of the substrate;

a monitor signal input waveguide disposed on the substrate ~~and having~~ comprising:

~~one~~ a first terminal connected to the monitor signal input port in the output

side slab-waveguide; and

~~the other a second~~ terminal disposed at a position other than the aforementioned predetermined position on the end face of the substrate; and

an optical fiber for optically inter-connecting the monitor signal output waveguide at one end of the substrate and the corresponding terminal of the monitor signal input waveguide.

15. (Currently Amended) An arrayed waveguide grating comprising:

a substrate;

input waveguides disposed on the substrate for inputting signals of individual wavelengths in correspondence thereto;

a channel waveguide grating disposed on the substrate ~~and having comprising~~ waveguides with lengths progressively increasing by a predetermined waveguide length difference;

an input side slab-waveguide disposed on the substrate and inter-connecting the input side of the channel waveguide array and the input waveguides;

an output side slab-waveguide connected to the output side of the channel waveguide array ~~and having comprising~~:

a wavelength multiplexed signal output port disposed at the focus position of the 0-th diffracted signals obtained from the signals inputted from the input waveguides through the input side slab-waveguide and the channel waveguide array; ; and

a monitor signal port disposed at the focus position of the higher order diffraction beams other than the 0-th order diffraction beams obtained from the signals inputted from the input waveguides;

an output waveguide disposed on the substrate ~~and having comprising~~:

one a first terminal connected to the monitor signal port of the output side slab-waveguide; and

~~the other a second~~ terminal disposed on ~~a predetermined position~~ an end face of the substrate;

an optical fiber ~~having~~ comprising:

~~one~~ a first terminal connected to the afore-mentioned ~~other~~ second terminal of the output waveguide located on the end face of the substrate; and

a reflecting means connected to ~~the other~~ a second terminal of the optical fiber for reflecting the signal led out from that other terminal.

16. (Currently Amended) An arrayed waveguide grating comprising:

input waveguides for inputting signals of individual wavelengths in correspondence to these wavelengths;

a channel waveguide array ~~having~~ comprising waveguides with lengths progressively increasing by a predetermined waveguide length difference;

a feedback waveguide for feeding back a multiplexed monitor signal;

an input side slab-waveguide, in which the input waveguides and the feedback waveguide are disposed and the input side of the channel waveguide array is disposed on the output side;

an output side slab-waveguide connected to the output side of the channel waveguide array ~~and~~ having comprising:

an output port disposed on the focus position of the 0-th diffraction beams obtained from the signal inputted from the input waveguides through the input side slab-waveguide and the channel waveguide array for outputting the wavelength multiplexed signal; ;

a feedback port disposed at the focus position of higher order diffraction beams other than the 0-th order obtained from the signals inputted from the input waveguides; and

at least one ~~or plurality~~ monitor signal ports for outputting monitor signals separated from the multiplexed signal inputted from the feedback waveguide through the channel waveguide array;

an output waveguide connected to the output port of the output side slab-waveguide; and

monitor signal output waveguide connected to the monitor signal port.

17. (Currently Amended) An arrayed waveguide grating comprising:

input waveguides for inputting signals of individual wavelengths in correspondence to these wavelengths;

a channel waveguide array ~~having~~ comprising waveguides with lengths progressively increasing by a predetermined waveguide length difference;

a feedback fiber for feeding back a multiplexed signal monitor signal;

an input side slab-waveguide, in which the input waveguides and the feedback fiber are disposed on one side and the input side of the channel waveguide array is disposed on the output side;

an output side slab-waveguide connected to the output side of the channel waveguide array ~~and having~~ comprising:

an output port disposed on the focus position of the 0-th diffraction beams obtained from the signal is inputted from the input waveguides through the input side slab-waveguide and the channel waveguide array for outputting the wavelength multiplexed signal; ;

a feedback port disposed at the focus position of higher order diffraction beams other than the 0-th order obtained from the signals inputted from the input waveguides ; and

at least one ~~or plurality~~ monitor signal ports for outputting monitor signals separated from the multiplexed signal inputted from the feedback fiber through the channel waveguide array;

an output waveguide connected to the output port of the output side slab-waveguide; and

monitor signal output waveguide connected to the monitor signal port.

18. (Currently Amended) An arrayed waveguide grating comprising:

input waveguides for inputting signals of individual wavelengths in correspondence to

these wavelengths;

monitor waveguides disposed at positions individual from the input waveguides for outputting monitor signals;

a channel waveguide array ~~having~~ comprising waveguides with lengths progressively increasing by a predetermined waveguide length difference;

an output side slab-waveguide connected to the output side of the channel waveguide array and including a signal returning means for causing a signal converged on the focus position of higher order diffraction beams other than the 0-th order obtained from the signals inputted from the input waveguides through the input side slab-waveguide and the channel waveguide array;

an input side slab-waveguide inter-connecting the input waveguides, the input side of the channel waveguide array and the monitor waveguides for outputting the signal inputted from the output side slab-waveguide through the channel waveguide array to the monitor signal waveguide;

an output port disposed on the output side slab-waveguide at the focus position of the 0-th diffraction beams obtained from the signal inputted from the input waveguides for outputting the wavelength multiplexed signal; and

an output waveguide connected to the output port.

19. (Original) The arrayed waveguide grating according to claim 18, wherein the monitor waveguide is disposed at the focus position of the 0-th order diffraction beams obtained from the signals returning from the output side slab-waveguide to the input side slab-waveguide, and the focus positions of the 1-st order diffraction beams are disposed at positions mid way between adjacent ones of the input waveguides.

20. (Original) The arrayed waveguide grating according to claim 18, wherein the monitor waveguides are disposed alternately with the input waveguides at the input side slab-waveguide.

21. (Original) The arrayed waveguide grating according to claim 18, wherein the input positions of the input side slab-waveguide corresponding to the individual wavelengths of the inputs inputted to the input waveguides are disposed mid way between the 0-th and 1-st diffraction beams returning from the channel waveguide array.

22. (Currently Amended) The arrayed waveguide grating according to claim 18, wherein a region covering the positions of the monitor signal ports in the input side slab-waveguide is set such that it does not overlap but is separate from a region covering the positions of the input ports.

23. (Currently Amended) The arrayed waveguide grating according to claim 18, wherein the signal returning means ~~includes~~ comprises:

a higher order diffraction beam reflecting mirror disposed in the output side slab-waveguide at the focus position of the higher order diffraction beams; ; and

a signal returning mirror disposed at a position other than the position of the higher order diffraction beam reflecting mirror and the focus position of the 0-th order diffraction beams for returning the signals reflected by the higher order diffraction beam mirror to the input slab-waveguide side.

24. (Currently Amended) The arrayed waveguide grating according to claim 18, wherein the signal returning means ~~includes~~ comprises:

a signal returning mirror disposed in the output side slab-waveguide at the focus position of the higher order diffraction beams for returning the higher order diffraction beams incident on that position along a path at a signal angle from the optical axis to the input slab-waveguide side.

25. (Currently Amended) The arrayed waveguide grating according to claim 18, wherein the signal returning means ~~includes~~ comprises:

a mirror disposed on one end face of a substrate with the output side slab-waveguide; ;

a first monitor signal waveguide for leading the signal converged on the focus position of the higher order diffraction beams to the afore-mentioned mirror; and

a second monitor signal waveguide, which causes the signal reflected by the afore-mentioned mirror to be inputted to the output side slab-waveguide from a position thereof other than the output port and thereof the focus position of the higher order diffraction beams other than the 0-th order for being outputted to the input slab-waveguide side.

26. (Currently Amended) The arrayed waveguide grating according to claim 18, wherein the signal returning means comprises a monitor signal waveguide, which the signal converged on the focus position of the higher order diffraction beams is inputted to and causes the inputted to be inputted to the output side slab-waveguide from a position thereof other than the output port and thereof the focus position of the higher order diffraction beams for being outputted to the input slab-waveguide side.

27. (Currently Amended) The arrayed waveguide grating according to claim 18, wherein the signal returning means ~~includes~~ comprises an optical fiber, which the signal converged on the focus position of the higher order diffraction beams is inputted to and causes the input to be inputted to the output side slab-waveguide from a position thereof other than the output port and thereof the focus position of the higher order diffractions beams for being outputted to the input slab-waveguide side.

28. (Currently Amended) An optical communication system comprising:

an optical communication means for outputting signal signals of individual wavelengths as parallel signals;

a multiplexer ~~constituted by~~ comprising an arrayed waveguide grating for wavelength multiplexing the signals of the individual wavelengths outputted from the optical communication means;

an optical transmission path for transmitting the wavelength multiplexed signal outputted from the multiplexer;

a node provided on the optical transmission path ~~and including~~ comprising an arrayed waveguide grating;

a demultiplexer ~~constituted by~~ comprising an arrayed waveguide grating for separating the individual wavelength signals from the signal inputted through the optical transmission path and the node thereon; and

an optical reception means for receiving the individual wave signals separated by the ~~multiplexer, and multiplexer,~~

the multiplexer ~~including~~ comprising:

a plurality of input waveguides for inputting signals of individual wavelengths in correspondence to these wavelengths; ; and

a slab-waveguide having a wavelength multiplexed signal output port disposed at the focus position of the 0-th order diffraction beams of the signals inputted from the input waveguides through an input side slab-waveguide and a channel waveguide array and monitor signal port disposed at the focus position of higher order diffraction beams other than the 0-th order obtained from the signals inputted from the input waveguides or monitoring the wavelength multiplexed signal.

29. (Currently Amended) An optical transmission system comprising a transmission path loop having comprising a plurality of nodes connected to one another by transmission paths such that a wavelength multiplexed signal is sent out to these transmission ~~paths; paths,~~

the nodes each ~~including~~ comprising:

a first arrayed waveguide grating for separating signals of individual wavelengths from the inputted wavelength multiplexed signal; and

a second arrayed wavelength waveguide grating for waveguide wavelength multiplexing the separated signal signals of the individual ~~wavelengths; wavelengths,~~

the second arrayed waveguide grating having comprising:

a plurality of input waveguides for inputting signals of individual wavelengths in correspondence to these signals; ; and

a slab-waveguide having comprising:

a wavelength multiplexed signal output port disposed at the focus position of the 0-th diffraction beams obtained from the signals inputted from the input waveguides through an input side slab-waveguide; and

a channel waveguide array and a monitor signal port disposed at the focus position of higher order diffraction beams other than the 0-th order obtained from the signals inputted from the input waveguides for monitoring the wavelength multiplexed signal.

30. (Currently Amended) An optical communication system comprising:

an optical communication means for outputting signal signals of individual wavelengths as parallel signals;

a multiplexer constituted by an arrayed waveguide grating for wavelength multiplexing the individual wavelength signals outputted from the optical communication means;

an optical transmission path for transmitting the wavelength multiplexed signal outputted from the multiplexer;

a node disposed on the optical transmission path ~~and including~~ comprising an arrayed waveguide grating; and

a demultiplexer for demultiplexing the signal inputted thereto along the optical transmission path and on the node thereon to separate the individual wavelength signals;

an optical reception means for receiving the separated individual wavelength signals from the ~~demultiplexer; and demultiplexer.~~

the demultiplexer ~~including~~ comprising:

a plurality of input waveguides; and

a slab waveguide ~~having~~ comprising:

a wavelength multiplexed signal output port disposed at the focus position of the 0-th order diffraction signals inputted from the input waveguides through an input side slab-waveguide and a channel waveguide array; ;

a higher order diffraction beam reflecting means disposed at the focus position of higher order diffraction beam positions other than the 0-th order obtained from the

signals inputted from the input waveguides for reflecting the higher order diffraction beams to the side of the plurality of input waveguides; and

at least one ~~or more~~ monitor signal ports disposed at a position or positions other than the ports of the plurality of input waveguides for inputting a signal or signals reflected by the higher order signal reflecting means.

31. (Currently Amended) An optical communication system comprising:

a transmission path loop ~~having~~ comprising a plurality of nodes connected to one another by transmission paths such that a wavelength multiplexed signal is sent out to these transmission ~~paths; paths,~~

the nodes each including comprising:

a first arrayed waveguide grating for separating signals of individual wavelengths from the inputted wavelength multiplexed signal; and

a second arrayed wavelength waveguide grating for waveguide wavelength multiplexing the separated signal signals of the individual ~~wavelengths; wavelengths,~~

the second arrayed waveguide grating having comprising:

a slab-waveguide which ~~includes~~ comprises:

a plurality of input waveguides for inputting signals of individual wavelengths in correspondence to these signals; ;

a multiplexed signal output port disposed at the focus position of the 0-th diffraction beams obtained from the signals inputted from the input waveguides through an input side slab-waveguide and a channel waveguide array; ;

a higher order diffraction beam reflecting means for reflecting the higher order diffraction beams to the side of the plurality of input waveguides; ~~and~~

a plurality of monitor signal ports disposed at positions other than the port positions of the plurality of input waveguides for inputting the signals reflected by the higher order diffraction beams; ; and

a monitor signal port disposed at the focus position of higher order diffraction beams other than the 0-th order obtained from the signals inputted from the input

waveguides for monitoring the wavelength multiplexed signal.

32. (New) The arrayed waveguide according to claim 1, further comprising:

a signal returning means disposed on a focus position of the higher order diffraction beam other than the 0-th order diffraction beam.

33. (New) The arrayed waveguide grating according to claim 32, wherein said signal returning means comprises:

a higher order diffraction beam reflecting means disposed on the focus position of higher order diffraction beams other than the 0-th order diffraction beam obtained from the signals inputted from the input ports for reflecting the higher order diffraction beams to the side of the plurality of input ports.

34. (New) The arrayed waveguide grating according to claim 2, wherein said slab-waveguide further comprises:

at least one monitor signal port.

35. (New) The arrayed waveguide grating according to claim 34, wherein said at least one monitor signal port comprises:

a monitor signal port disposed on a focus position of higher order diffraction beams other than the 0-th order diffraction beam obtained from the signals inputted from the input ports for monitoring the multiplexed signal.

36. (New) The arrayed waveguide grating according to claim 34, wherein said at least one monitor signal port comprises:

at least one monitor signal port disposed at positions other than the plurality of input ports for taking out at least one signal reflected from the higher order diffraction beam reflecting means.

37. (New) The arrayed waveguide grating according to claim 34, wherein said at least one monitor signal port comprises:

at least one monitor signal port disposed at positions corresponding to the plurality of input ports for taking out at least one signal reflected from the higher order diffraction beam reflecting means.

38. (New) The arrayed waveguide grating according to claim 2, wherein said higher order diffraction beam reflecting means comprises:

at least one reflecting mirror disposed such that the reflecting surfaces of said at least one reflecting mirror face said input ports.

39. (New) The arrayed waveguide grating according to claim 38, wherein said at least one reflecting mirror comprises:

a first reflecting mirror; and
a second reflecting mirror.

40. (New) An arrayed waveguide grating comprising:

an input side slab-waveguide interconnecting a plurality of input waveguides and having monitor signal ports for monitoring signals returning to said input side slab-waveguide; and

an output side slab-waveguide comprising an output port disposed at the focus position of the 0-th order diffraction beams inputted from the input waveguides through said input side slab-waveguide for outputting a wavelength multiplexed signal.

Serial No. 09/987,633
Docket No.: 2000P348871
FUK.016

25

AMENDMENTS TO THE DRAWINGS:

The attached sheets of drawings include changes to Figures 25 and 26 to overcome the Examiner's objections by including the legend "PRIOR ART" on each figure. These sheets which include Figures 25 and 26 replace the original sheets which include Figures 25 and 26.

Attachments: Replacement Sheets
Annotated Sheets Showing Changes